

Dancik Open-WebService Reference

Function ID/Path : /cn/getAllContacts

This function retrieves contacts. If contactid/groupid/fullacct are left blank, all contacts are retrieved.

Inputs :

Variable	Type	Req?	Description
contactid	string(20)	N	Contact id
groupid	string(20)	N	Group id
fullacct	string(20)	Y	Account Number
association	string(20)		
maxrows			
startingRecord			
orderby			
orderby_desc			

Example (XML) :

```
<dancik-api-request>
  <contactid> XXX </contactid>
  <groupid> XXX </groupid>
  <fullacct> XXX </fullacct>
  <association> XXX </association>
  <maxrows> XXX </maxrows>
  <startingRecord> XXX </startingRecord>
  <orderby> XXX </orderby>
  <orderby_desc> XXX </orderby_desc>
</dancik-api-request>
```

Example (JSON) :

```
{
  "contactid": " XXX ",
  "groupid": " XXX ",
  "fullacct": " XXX ",
  "association": " XXX ",
  "maxrows": " XXX ",
  "startingRecord": " XXX ",
  "orderby": " XXX ",
  "orderby_desc": " XXX "
}
```

Outputs :

Layout name : contactinfo

Variable	Type	Description
Name	string	Name of contact
notes	string	Notes

Example (XML) :

```
<dancik-api-response>
  <contactinfo>
    <Name> XXX </Name>
    <notes> XXX </notes>
  </contactinfo>
</dancik-api-response>
```

Example (JSON) :

```
{
  "contactinfo": [{
    "Name": " XXX ",
    "notes": " XXX "
  }]
}
```

History :

Date	Description
10/16/2015	Retrieve contacts