

Dancik Open-WebService Reference

Function ID/Path : /d24/getInit_OrderDetails

This function is specific to the Dancik Decor24 Order Details screen.

Inputs :

| Variable | Type | Req? | Description |
|-----------------|------------|------|--|
| d24user | string(10) | Y | The login profile name. |
| d24sesid | string(20) | Y | The logged in users active session id. |
| d24_referenceid | integer(7) | Y | Reference# |

Example (XML) :

```
<dancik-api-request>
  <d24user> XXX </d24user>
  <d24sesid> XXX </d24sesid>
  <d24_referenceid> XXX </d24_referenceid>
</dancik-api-request>
```

Example (JSON) :

```
{
  "d24user": " XXX ",
  "d24sesid": " XXX ",
  "d24_referenceid": " XXX "
}
```

Outputs :

Layout name : header

| Variable | Type | Description |
|-----------------------|---------|---|
| reference | integer | Reference# |
| po | string | Purchase Order# |
| tag | string | Tag line |
| orderdate | string | Order Date (formatted to MM/DD/YY) |
| shipdate | string | Ship Date (formatted to MM/DD/YY) |
| status_description | string | The status description the order is currently in. |
| shipvia | string | Ship Via id#. |
| shipvia_description | string | Ship Via description. |
| special_instructions1 | string | Special Instructions 1 |
| special_instructions2 | string | Special Instructions 2 |
| shipping_instructions | string | Shipping Instructions |
| shipto_name | string | ShipTo Name |
| shipto_address1 | string | ShipTo Address 1 |
| shipto_address2 | string | ShipTo Address 2 |
| shipto_city | string | ShipTo City |
| shipto_state | string | ShipTo State |
| shipto_countrycode | string | ShipTo Country Code |
| shipto_dsp_zipcode | string | ShipTo Zipcode (for displaying) |
| shipto_zipcode5 | string | ShipTo Zipcode (5-digits) |
| shipto_zipcode4 | string | ShipTo Zipcode (4-digits) |
| shipto_zipcode7 | string | ShipTo Zipcode (7-digits - Canadian) |
| additional_msg01 | string | Additional Messages 1 |
| additional_msg02 | string | Additional Messages 2 |
| additional_msg03 | string | Additional Messages 3 |
| additional_msg04 | string | Additional Messages 4 |

Dancik Open-WebService Reference

Function ID/Path : /d24/getInit_OrderDetails

This function is specific to the Dancik Decor24 Order Details screen.

| Variable | Type | Description |
|------------------|--------|---|
| additional_msg05 | string | Additional Messages 5 |
| ordercontact | string | Order Contact |
| jobname | string | Job Name |
| canadian_flag | string | Canadian Flag (= Y is ship to address is canadian) |
| backordered | string | Back Ordered flag (= Y if any item on the order is backordered) |

Layout name : details

| Variable | Type | Description |
|-----------------------|---------|---|
| line | integer | Order Line# |
| dsp_line | string | Order Line# (formatted for display) |
| item | string | Native Dancik Item# |
| dsp_item | string | Item# following Cust Item logic |
| item_description | string | Item Description following Cust Item logic |
| uom | string | Unit of measure of the quantity ordered. |
| serial | string | Serial#. |
| item_status | string | Order status for the line item. |
| price | decimal | Unit price |
| dsp_price | string | Unit price (formatted for display) |
| extended_price | decimal | Extended price |
| dsp_extended_price | string | Extended price (formatted for display) |
| quantity_ordered | decimal | Quantity of units ordered. |
| dsp_quantity_ordered1 | string | Quantity and units of measure, formatted for display) |
| dsp_quantity_ordered2 | string | Converted quantity and units of measure, formatted for display) |
| credited_flag | string | Credit flag (= Y if the line is considered a credit) |
| dyelot | string | Dyelot |
| warehouse | string | Shipping warehouse |
| sidemark_1 | string | Sidemark / Comment 1 |
| sidemark_2 | string | Sidemark / Comment 2 |
| sidemark_3 | string | Sidemark / Comment 3 |
| sidemark_4 | string | Sidemark / Comment 4 |
| sidemark_5 | string | Sidemark / Comment 5 |
| sidemark_6 | string | Sidemark / Comment 6 |
| sidemark_7 | string | Sidemark / Comment 7 |
| sidemark_8 | string | Sidemark / Comment 8 |
| sidemark_9 | string | Sidemark / Comment 9 |
| invoice | string | Invoice, if there is one. |
| backorder_date | string | Backorder date, if there is one. (formatted to MM/DD/YY) |
| bill_of_lading | string | Bill of lading, if there is one. |

Dancik Open-WebService Reference

Function ID/Path : /d24/getInit_OrderDetails

This function is specific to the Dancik Decor24 Order Details screen.

Layout name : shipvias

| Variable | Type | Description |
|----------|--------|--------------------------|
| id | string | Ship-Via identifier/key. |
| id | string | Ship-Via description. |

Layout name : contacts

| Variable | Type | Description |
|----------|--------|---------------------|
| contact | string | Contact description |

Layout name : states

| Variable | Type | Description |
|-------------|--------|---------------------|
| id | string | State abbreviation. |
| description | string | Full Name of State |

Example (XML) :

```
<dancik-api-response>
  <header>
    <reference> XXX </reference>
    <po> XXX </po>
    <tag> XXX </tag>
    <orderdate> XXX </orderdate>
    <shipdate> XXX </shipdate>
    <status_description> XXX </status_description>
    <shipvia> XXX </shipvia>
    <shipvia_description> XXX </shipvia_description>
    <special_instructions1> XXX </special_instructions1>
    <special_instructions2> XXX </special_instructions2>
    <shipping_instructions> XXX </shipping_instructions>
    <shipto_name> XXX </shipto_name>
    <shipto_address1> XXX </shipto_address1>
    <shipto_address2> XXX </shipto_address2>
    <shipto_city> XXX </shipto_city>
    <shipto_state> XXX </shipto_state>
    <shipto_countrycode> XXX </shipto_countrycode>
    <shipto_dsp_zipcode> XXX </shipto_dsp_zipcode>
    <shipto_zipcode5> XXX </shipto_zipcode5>
    <shipto_zipcode4> XXX </shipto_zipcode4>
    <shipto_zipcode7> XXX </shipto_zipcode7>
    <additional_msg01> XXX </additional_msg01>
    <additional_msg02> XXX </additional_msg02>
    <additional_msg03> XXX </additional_msg03>
    <additional_msg04> XXX </additional_msg04>
    <additional_msg05> XXX </additional_msg05>
    <ordercontact> XXX </ordercontact>
    <jobname> XXX </jobname>
    <canadian_flag> XXX </canadian_flag>
    <backordered> XXX </backordered>
  </header>
  <details>
    <line> XXX </line>
    <dsp_line> XXX </dsp_line>
    <item> XXX </item>
    <dsp_item> XXX </dsp_item>
    <item_description> XXX </item_description>
    <uom> XXX </uom>
    <serial> XXX </serial>
    <item_status> XXX </item_status>
    <price> XXX </price>
```

Example (JSON) :

```
{
  "header" : {
    "reference" : " XXX ",
    "po" : " XXX ",
    "tag" : " XXX ",
    "orderdate" : " XXX ",
    "shipdate" : " XXX ",
    "status_description" : " XXX ",
    "shipvia" : " XXX ",
    "shipvia_description" : " XXX ",
    "special_instructions1" : " XXX ",
    "special_instructions2" : " XXX ",
    "shipping_instructions" : " XXX ",
    "shipto_name" : " XXX ",
    "shipto_address1" : " XXX ",
    "shipto_address2" : " XXX ",
    "shipto_city" : " XXX ",
    "shipto_state" : " XXX ",
    "shipto_countrycode" : " XXX ",
    "shipto_dsp_zipcode" : " XXX ",
    "shipto_zipcode5" : " XXX ",
    "shipto_zipcode4" : " XXX ",
    "shipto_zipcode7" : " XXX ",
    "additional_msg01" : " XXX ",
    "additional_msg02" : " XXX ",
    "additional_msg03" : " XXX ",
    "additional_msg04" : " XXX ",
    "additional_msg05" : " XXX ",
    "ordercontact" : " XXX ",
    "jobname" : " XXX ",
    "canadian_flag" : " XXX ",
    "backordered" : " XXX "
  }
  "details" : [ {
    "line" : " XXX ",
    "dsp_line" : " XXX ",
    "item" : " XXX ",
    "dsp_item" : " XXX ",
    "item_description" : " XXX ",
    "uom" : " XXX ",
    "serial" : " XXX ",
    "item_status" : " XXX ",
    "price" : " XXX ",
```

Dancik Open-WebService Reference

Function ID/Path : /d24/getInit_OrderDetails

This function is specific to the Dancik Decor24 Order Details screen.

```

<dsp_price> XXX </dsp_price>
<extended_price> XXX </extended_price>
<dsp_extended_price> XXX </dsp_extended_price>
<quantity_ordered> XXX </quantity_ordered>
<dsp_quantity_ordered1> XXX </dsp_quantity_ordered1>
<dsp_quantity_ordered2> XXX </dsp_quantity_ordered2>
<credited_flag> XXX </credited_flag>
<dyelot> XXX </dyelot>
<warehouse> XXX </warehouse>
<sidemark_1> XXX </sidemark_1>
<sidemark_2> XXX </sidemark_2>
<sidemark_3> XXX </sidemark_3>
<sidemark_4> XXX </sidemark_4>
<sidemark_5> XXX </sidemark_5>
<sidemark_6> XXX </sidemark_6>
<sidemark_7> XXX </sidemark_7>
<sidemark_8> XXX </sidemark_8>
<sidemark_9> XXX </sidemark_9>
<invoice> XXX </invoice>
<backorder_date> XXX </backorder_date>
<bill_of_lading> XXX </bill_of_lading>
</details>
<shipvias>
  <id> XXX </id>
  <id> XXX </id>
</shipvias>
<contacts>
  <contact> XXX </contact>
</contacts>
<states>
  <id> XXX </id>
  <description> XXX </description>
</states>
</dancik-api-response>

```

```

"dsp_price": " XXX ",
"extended_price": " XXX ",
"dsp_extended_price": " XXX ",
"quantity_ordered": " XXX ",
"dsp_quantity_ordered1": " XXX ",
"dsp_quantity_ordered2": " XXX ",
"credited_flag": " XXX ",
"dyelot": " XXX ",
"warehouse": " XXX ",
"sidemark_1": " XXX ",
"sidemark_2": " XXX ",
"sidemark_3": " XXX ",
"sidemark_4": " XXX ",
"sidemark_5": " XXX ",
"sidemark_6": " XXX ",
"sidemark_7": " XXX ",
"sidemark_8": " XXX ",
"sidemark_9": " XXX ",
"invoice": " XXX ",
"backorder_date": " XXX ",
"bill_of_lading": " XXX "
}]
"shipvias": [{
  "id": " XXX ",
  "id": " XXX "
}]
"contacts": [{
  "contact": " XXX "
}]
"states": [{
  "id": " XXX ",
  "description": " XXX "
}]
}]
}

```

History :

| Date | Description |
|------------|-------------|
| 07/05/2011 | New Call |