

# Dancik Open-WebService Reference

## Function ID/Path : /des/releaseSpoolFile

This function releases a spool file that was created with HOLD(\*YES)

### Inputs :

Variable	Type	Req?	Description
parm_job	string(10)	Y	JobName
parm_User	string(10)	Y	JobUser
parm_jobnumber	string(6)	Y	Job Number
parm_PrinterFile	string(10)	Y	Spool File Name
parm_SpoolFile	string(6)	Y	Spool File Number

#### Example (XML) :

```
<dancik-api-request>
  <parm_job> XXX </parm_job>
  <parm_User> XXX </parm_User>
  <parm_jobnumber> XXX </parm_jobnumber>
  <parm_PrinterFile> XXX </parm_PrinterFile>
  <parm_SpoolFile> XXX </parm_SpoolFile>
</dancik-api-request>
```

#### Example (JSON) :

```
{
  "parm_job": " XXX ",
  "parm_User": " XXX ",
  "parm_jobnumber": " XXX ",
  "parm_PrinterFile": " XXX ",
  "parm_SpoolFile": " XXX "
}
```

### Outputs :

Layout name : records

Variable	Type	Description
id	string	Record Id
description	string	Description of the ID

#### Example (XML) :

```
<dancik-api-response>
  <records>
    <id> XXX </id>
    <description> XXX </description>
  </records>
</dancik-api-response>
```

#### Example (JSON) :

```
{
  "records": [{
    "id": " XXX ",
    "description": " XXX "
  }]
}
```

### History :

Date	Description
05/18/2015	Release Spool File