

Dancik Open-WebService Reference

Function ID/Path : /fm/setAttributes

This function calls the I/O service program associated with a particular Packing Class attributes. The attributes will be added or deleted according to the action code(s) provided.

Inputs :

Variable	Type	Req?	Description
packaging_class	character(6)	Y	Packaging Class Code.
attr_number	array	Y	Attribute Number.
attr_value	array	Y	Attribute Value.
action	array	Y	Action Code (A/D).

Example (XML) :

```
<dancik-api-request>
  <packaging_class> XXX </packaging_class>
  <attr_number> XXX </attr_number>
  <attr_value> XXX </attr_value>
  <action> XXX </action>
</dancik-api-request>
```

Example (JSON) :

```
{
  "packaging_class": " XXX ",
  "attr_number": " XXX ",
  "attr_value": " XXX ",
  "action": " XXX "
}
```

Outputs :

Layout name : success

Variable	Type	Description
time_stamp	timestamp	Timestamp of the successful request

Example (XML) :

```
<dancik-api-response>
  <success>
    <time_stamp> XXX </time_stamp>
  </success>
</dancik-api-response>
```

Example (JSON) :

```
{
  "success": {
    "time_stamp": " XXX "
  }
}
```

History :

Date	Description
01/26/2015	New Call