

Dancik Open-WebService Reference

Function ID/Path : /is/setFilterViewDefault

Set a new default filter or view for a user.

Inputs :

Variable	Type	Req?	Description
dftid	dec(9,0)	Y	Default Key Identifier
appid	string(10)	Y	Application ID
tableid	string(50)	Y	Table ID
type	string(1)	Y	Filter/View (F/V)
default_flag	string(1)	Y	Default Flag (Y)

Example (XML) :

```
<dancik-api-request>
  <dftid> XXX </dftid>
  <appid> XXX </appid>
  <tableid> XXX </tableid>
  <type> XXX </type>
  <default_flag> XXX </default_flag>
</dancik-api-request>
```

Example (JSON) :

```
{
  "dftid": " XXX ",
  "appid": " XXX ",
  "tableid": " XXX ",
  "type": " XXX ",
  "default_flag": " XXX "
}
```

Outputs :

Layout name : success

Variable	Type	Description
time_stamp	timestamp	Timestamp of the successful request

Example (XML) :

```
<dancik-api-response>
  <success>
    <time_stamp> XXX </time_stamp>
  </success>
</dancik-api-response>
```

Example (JSON) :

```
{
  "success": {
    "time_stamp": " XXX "
  }
}
```

History :

Date	Description
10/19/2015	New Call