

Dancik Open-WebService Reference

Function ID/Path : /d24/getShipToAddresses

The function builds a result set of available ship to addresses based on the users associated account.

Inputs :

Variable	Type	Req?	Description
d24user	string(10)	Y	The login profile name.
d24sesid	string(20)	Y	The logged in users active session id.

Example (XML) :

```
<dancik-api-request>
  <d24user> XXX </d24user>
  <d24sesid> XXX </d24sesid>
</dancik-api-request>
```

Example (JSON) :

```
{
  "d24user": " XXX ",
  "d24sesid": " XXX "
}
```

Outputs :

Layout name : shiptos

Variable	Type	Description
id	string	Ship-To identifier/key
name	string	Name
address1	string	Address 1
address2	string	Address 2
city	string	City
state	string	State
zipcode	string	Formatted zipcode, based on values
zipcode5	string	Zip Code (5 of 5-4)
zipcode4	string	Zip Code (4 of 5-4)
zipcode7	string	Canadian Zip Code

Example (XML) :

```
<dancik-api-response>
  <shiptos>
    <id> XXX </id>
    <name> XXX </name>
    <address1> XXX </address1>
    <address2> XXX </address2>
    <city> XXX </city>
    <state> XXX </state>
    <zipcode> XXX </zipcode>
    <zipcode5> XXX </zipcode5>
    <zipcode4> XXX </zipcode4>
    <zipcode7> XXX </zipcode7>
  </shiptos>
</dancik-api-response>
```

Example (JSON) :

```
{
  "shiptos": [ {
    "id": " XXX ",
    "name": " XXX ",
    "address1": " XXX ",
    "address2": " XXX ",
    "city": " XXX ",
    "state": " XXX ",
    "zipcode": " XXX ",
    "zipcode5": " XXX ",
    "zipcode4": " XXX ",
    "zipcode7": " XXX "
  } ]
}
```

History :

Dancik Open-WebService Reference

Function ID/Path : /d24/getShipToAddresses

The function builds a result set of available ship to addresses based on the users associated account.

Date	Description
09/14/2011	New Call