

Dancik Open-WebService Reference

Function ID/Path : /invoicing/createInvoices

Create Invoices from Orders

Inputs :

| Variable | Type | Req? | Description |
|-------------------------|-----------|------|--|
| order_numbers | array | Y | Array of order numbers |
| company_number | string(1) | N | Company number |
| branch | string(3) | N | Branch id |
| override_invoice_date | string(8) | N | Date to override invoice date |
| override_company_number | string(1) | N | Company Number to override |
| override_printer_id | string(2) | N | Printer ID to override printer ID |
| run_invoices_for | string(1) | Y | Run invoices for user selections or all selections |
| print_option | string(1) | Y | Print option for the report/creation process |

Example (XML) :

```
<dancik-api-request>
  <order_numbers> XXX </order_numbers>
  <company_number> XXX </company_number>
  <branch> XXX </branch>
  <override_invoice_date> XXX </override_invoice_date>
  <override_company_number> XXX </override_company_number>
  <override_printer_id> XXX </override_printer_id>
  <run_invoices_for> XXX </run_invoices_for>
  <print_option> XXX </print_option>
</dancik-api-request>
```

Example (JSON) :

```
{
  "order_numbers": " XXX ",
  "company_number": " XXX ",
  "branch": " XXX ",
  "override_invoice_date": " XXX ",
  "override_company_number": " XXX ",
  "override_printer_id": " XXX ",
  "run_invoices_for": " XXX ",
  "print_option": " XXX "
}
```

Outputs :

Layout name : success

| Variable | Type | Description |
|------------|-----------|-------------------------------------|
| time_stamp | timestamp | Timestamp of the successful request |

Example (XML) :

```
<dancik-api-response>
  <success>
    <time_stamp> XXX </time_stamp>
  </success>
</dancik-api-response>
```

Example (JSON) :

```
{
  "success": {
    "time_stamp": " XXX "
  }
}
```

History :

| Date | Description |
|----------|-------------|
| 11/06/13 | New Call |